

B200018



- ▶ 主要技术特性 (Main Specifications)
- ▶ 适用导线规格 (Applicable wire) : AWG30#~24#
- ▶ 适用基板厚度 (Applicable PC board thickness) : 0.8mm~1.6mm
- ▶ 温度范围 (Temperature range) : -25°C~+85°C
- ▶ 额定电压 (Voltage rating) : 250V AC, DC
- ▶ 额定电流 (Current rating) : 2A AC, DC
- ▶ 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- ▶ 绝缘电阻 (Insulation resistance) : $\geq 1000\Omega$
- ▶ 耐压 (Withstanding voltage) : 800V AC/minute

材料及电镀规格 Material and Finish

型号 Type	材料 Material	材料厚度 Material Thickness	电镀规格 Finish
孔座 HOUSING	PA66 UL94V-0	—	N/A
端子 TERMINAL	锡青铜 Phosphor bronze	0.2mm	镀锡 Tin-plated

产品尺寸图 Product size chart

 单位: mm 一般公差: ± 0.20

HOUSING

B200018-2



HOUSING

极数 Circuits	型号 Type	尺寸(Dimensions)mm		备注型号 P. S. Type
		A	B	
2	B200018-2-02	2.0	4.3	SM02B-PASS-TBT
3	B200018-2-03	4.0	6.3	SM03B-PASS-TBT
4	B200018-2-04	6.0	8.3	SM04B-PASS-TBT
5	B200018-2-05	8.0	10.3	SM05B-PASS-TBT
6	B200018-2-06	10.0	12.3	SM06B-PASS-TBT
7	B200018-2-07	12.0	14.3	SM07B-PASS-TBT
8	B200018-2-08	14.0	16.3	SM08B-PASS-TBT
9	B200018-2-09	16.0	18.3	SM09B-PASS-TBT
10	B200018-2-10	18.0	20.3	SM10B-PASS-TBT